

Highlights:

- Highflex™ solid & flexible jacket
- 4 mm² (11 AWG) thin and dense stranded conductors
- 10.2 mm (Ø) outer diameter

Product information:

The PLS240 is a high quality loudspeaker cable consisting of two 4.0 mm² (11 AWG) conductors composed with 226 copper strands of 0.15 mm thickness. The combination of thin and dense strands with high purity copper and the flexible and solid PVC outer jacket makes it the perfect cable for various kinds of applications. The smooth outer jacket provides great ease of installation for fixed systems while having perfect rolling & unrolling performance for highly demanding mobile applications.



Inner Conductors:



Usage:

RENTAL

Physical Characteristics:

Inner conductor	Insulation	Material	PVC 3.8 mm (Ø)
		Colours	Red / Blue
Outer jacket	Material		HighFlex™ NBR 10.2 mm (Ø)
	Colours		Black
Type of cable			2-core loudspeaker cable
Inner conductor	Material		BC 226 x 0.15 mm (Ø) (OFC)
	Section		4 mm ²
	American Wire Gauge		11 AWG
	Number of conductors		2


Mechanical Characteristics:

Temperature range	Fixed installation	- 15 °C till + 70 °C
	Mobile installation	- 5 °C till + 70 °C
Bending radius	Fixed installation	5 x outer diameter
	Mobile installation	10 x outer diameter

Electrical Characteristics:

Max. conductor	DC resistance	4.95 (Ω / Km)
Resistance	Insulation	> 500 M Ω / km
Dielectric strength		2 (KV / 1 min. DC)
Rated voltage		500 V

Cross sections:



Variants:

- PLS240/1 - 100 meter
- PLS240/3 - 300 meter